# Tellerstift Pistole (CD) AS 1811

**Artikel nr. AS 1811 : 197 10 008 (Direkte Auslösung über Schalter)**

Zubehör finden Sie im Zubehörkatalog

## Isolieranwendungen mit Spitzenzündung (Kontaktverfahren)

Diese Pistole kann mit dem AS ISO eingesetzt werden (oder Geräte Serie MC). Sie eignet sich ausschließlich für das Verschweißen von Tellerstiften und Isoliernägeln. Durch die extrem präzise Kugelführung wird ein Höchstmaß an Reproduzierbarkeit erreicht.

| Technische Daten | AS 1811 |
|---|---|
| Schweißbereich *[Wird primär durch Schweißstromquelle bestimmt]* | Tellerstifte Ø 2,7mm mit Teller Ø 30/38mm<br>Iso-Nägel Ø 2/3mm in ST,Va,Al |
| Material | MaterialStahl, rostfreier Stahl Ø2-2,7<br>Aluminum Ø2-2,7 |
| Schweißstromquelle | Kondensator (CD) |
| Schweißzeit | 1-4ms, je nach Schweißeinstellung und Durchmesser |
| Schweißkabelanschluss | 7 pole |
| Gewicht | 0,95kg ohne Kabel |
| Länge | 220 mm |
| Aufnahmedurchmesser vorne | Ø32mm |
| Bolzenhalteraufnahme | Ø10mm |
| Zubehör | Mitgelieferte Andruckvorrichtung/ Magnetbolzenhalter |

- **Kugelführung (spielfrei)**
- **langes Schweißkabel 10 m**
- **Parametereinstellung ohne Werkzeug möglich**
- **7-poliger Steuerkabelanschluss**
- **Robuste 50qmm Schweißkabel-kupplung**

## 1811 geeignet für:

1200 | 1266 | 1066 Iso

**Wullener Feld 48 58454 Witten** **Info@bolzenschweissen.de** **Bestellhotline: +49 2302 95640-0**

# isolation gun (CD) AS 1811

**articel no. AS 1811: 197 10 008 (direct trigger over switch only)**

**equipment you can find in the associated prospect**

## Isolation application with Capacitor discharge studwelding (contact procedure)

This tried and tested studwelding gun is suitable for all AS CD studwelding units. This pistol can speacially be used for welding operations with cupped pins or iso-nails. With the precise rollerball guide it is possibel to do precise and reproducible welding operations.

| technical data | AS 1811 |
|---|---|
| welding range *[depending on studwelder]* | Disc pins Ø 2,7mm mit head Ø 30/38mm<br>Iso-nails Ø 2/ 3mm out of ST,Va,Al |
| material | steel, stainless steel Ø2-2,7<br>aluminium Ø2-2,7 |
| suitable power source | capacitor discharge units |
| welding time | 1-4ms, depending on welding parameter and stud diameter |
| weldcable plug | 7 poles |
| weight | 0,95kg without cabel |
| length | 220 mm |
| tool attachment diameter | Ø32mm |
| chuck attachment dimension | Ø10mm |
| equipment | added pressure unit / magnetic |

- **Rollertball guide (Zero clearance)**
- **long welding cable 10m**
- **intuitively operation and adjusting with only one turn switch**
- **7-Pole control cable connector**
- **tough 50smm cable plug**

## 1811 suitable for:

1200 | 1266 | 1066 Iso

**Wullener Feld 48 58454 Witten** **Info@bolzenschweissen.de** **hotline: +49 2302 95640-0**